

IN THE CLAIMS:

Please amend the claim as follows:

1. (Currently Amended) A thulium-doped fiber amplifier comprising:
 - a thulium-doped fiber to amplify optical signals belonging to S-band;
 - a first pumping unit configured to output an amplified spontaneous emission including an amplified filtered amplified spontaneous emission that represents a peak value in a predetermined wavelength range belonging to C-band to pump the thulium-doped fiber; and
 - a second pumping unit to output pumping light belonging to the C-band and a different wavelength band to pump the thulium-doped fiber.

2. (Original) The thulium-doped fiber amplifier according to claim 1, wherein the first pumping unit comprises:
 - an erbium-doped fiber to generate an amplified spontaneous emission;
 - a second wavelength selective coupler to combine inputted optical signals and the amplified spontaneous emission;
 - a splitter, coupled to form a loop as a circulating path of the amplified spontaneous emission and the second wavelength selective coupler, to split and output power of the amplified spontaneous emission and the optical signals; and
 - a filter, disposed on the loop, to filter the circulating amplified spontaneous emission based on a predetermined transmission wavelength belonging to the C-band.

3. (Original) The thulium-doped fiber amplifier according to claim 1, wherein the first pumping unit includes a pump laser diode outputting light at a predetermined wavelength.

4. (Original) The thulium-doped fiber amplifier according to claim 1, wherein the second pumping unit includes a pump laser diode outputting light at a predetermined wavelength.

5. (Original) The thulium-doped fiber amplifier according to claim 4, wherein the predetermined wavelength for the first and second pumping units is 0.98 μm .

6. (Currently Amended) A thulium-doped fiber amplifier comprising:

a thulium-doped fiber to amplify optical signals in an S-band;

a first pumping unit to generate an amplified spontaneous emission including an amplified filtered amplified spontaneous emission to pump the thulium-doped fiber, and disposed to form a loop in a circulating path of the amplified spontaneous emission wherein the amplified spontaneous emission represents a peak value in a preset wavelength range belonging to C-band, is generated by filtering the circulating amplified spontaneous emission; and

a second pumping unit to output pumping light to pump the thulium-doped fiber.

7. (Original) A thulium-doped fiber amplifier according to claim 3, wherein the first pumping unit comprises:

an erbium-doped fiber to generate an amplified spontaneous emission;

a second wavelength selective coupler, disposed on one side of the erbium-doped fiber, to combine the inputted optical signals and amplified spontaneous emission;

a splitter, disposed on the other side of the erbium-doped fiber, to form a loop of the amplified spontaneous emission and the second wavelength selective coupler, to split and output power of the amplified spontaneous emission and the optical signals; and

a filter, disposed on the loop, to filter and output the circulating amplified spontaneous emission based on a predetermined transmission wavelength belonging to the C-band.

8. (Original) A thulium-doped fiber amplifier according to claim 4, wherein the first pumping unit further comprises:

a first pumping light source to output pumping light to pump the erbium-doped fiber; and

a first wavelength selective coupler to combine the pumping light with the power of the erbium-doped fiber.

9. (Original) A thulium-doped fiber amplifier according to claim 4, wherein the first pumping unit further comprises a first isolator, disposed on the loop, to transmit the amplified spontaneous emission in one direction.

10. (Original) A thulium-doped fiber amplifier according to claim 3, wherein the second pumping unit comprises:

a second pumping light source to output pumping light belonging to the C-band and a different wavelength band to pump the thulium-doped fiber; and

a third wavelength selective coupler to combine the pumping light with the power of the thulium-doped fiber.

11. (Original) A thulium-doped fiber amplifier according to claim 1, further comprises a second isolator, disposed between the first and second pumping units, to block light inputted from the side of the thulium-doped fiber, wherein the first pumping unit is disposed in the front of the thulium-doped fiber and performs front-pumping of the thulium-doped fiber.

12. (Original) A thulium-doped fiber amplifier according to claim 3, wherein the first pumping unit is disposed in the rear of the thulium-doped fiber and performs rear-pumping of the thulium-doped fiber.